

colour code DIN 47100, EMC-preferred type


HELUKABEL® PAAR-TRONIC-CY-CY 6x2x0,34 QMM / 21094 CE

TECHNICAL DATA
PVC data cable in alignment with DIN VDE 0812

Temperature range	flexible -5°C to +80°C fixed -40°C to +80°C
Peak operating voltage	0.14 mm ² : 350 V 0.25 - 0.5 mm ² : 500 V (not for high power current installation purposes)
Test voltage core/core	0.14 mm ² : 1200 V 0.25 - 0.5 mm ² : 2000 V
Test voltage core/screen	800 V
Breakdown voltage	0.14 mm ² : 2400 V 0.25 - 0.5 mm ² : 4000 V
Mutual capacitance core/core	at 800 Hz 0.14 mm ² : approx. 147 pF/m 0.25 mm ² : approx. 152 pF/m
Mutual capacitance core/screen	at 800 Hz 0.14 mm ² : approx. 220 pF/m 0.25 mm ² : approx. 263 pF/m
Capacitive coupling k₁	at 800 Hz, max. 250 pF/100m
Coupling resistance	at 30 MHz, approx. 250 Ohm/km
Minimum bending radius	flexible 12x Outer-Ø fixed 6x Outer-Ø

■ CABLE STRUCTURE

- Copper wire bare, 0.5 mm²: finely stranded acc. to DIN VDE 0295 Class 5 / IEC 60228 Class 5
- Wire structure:
0.14 mm²: approx. 18 x 0.1 mm
0.25 mm²: approx. 14 x 0.15 mm
0.34 mm²: 7 x 0.25 mm
- Core insulation: PVC acc. to DIN VDE 0207-363-3 / DIN EN 50363-3 (compound type T12)
- Core identification acc. to DIN 47100 (paired stranding), colour coded
- x = without protective conductor
- Cores stranded in pairs with optimal lay lengths

- Screening element: pairs, braided screen of tinned copper wires, approx. coverage 85%
- PVC sheath over each screened pair
- Pairs stranded in layers with optimal lay lengths
- Foil wrapping
- Screen: braided screen of tinned copper wires, approx. coverage 85%
- Outer sheath: PVC acc. to DIN VDE 0207-363-4-1 / DIN EN 50363-4-1 (compound type TM2)
- Sheath colour: grey (RAL 7001)
- Length marking: in metres

■ PROPERTIES

- largely resistant to: oil, for details, see "Technical Information"
- the materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers

■ TESTS

- flame-retardant acc. to DIN VDE 0482-332-1-2 / DIN EN 60332-1-2 / IEC 60332-1-2
- certifications and approvals: EAC

■ APPLICATION

Used as a control and signal cable in electronic engineering, measurement and control technology. It provides interference-free transmission of data signals from peripheral equipment to information storage. Excellent connection cable for sound mixers, studio equipment and measurement and control technology. Reliable in process control, machining centres and safety-related systems. These cables with copper screening are ideally suited for interference-free data and signal transmission for measurement and control technology. EMC = Electromagnetic Compatibility; in order to optimise EMC properties, we recommend a double-sided and all-round large contact area of the copper braiding.

■ NOTES

- the conductor is metrically (mm²) constructed, AWG numbers are approximated, and are for reference only

Part no.	No. cores x cross-sec. mm ²	AWG, approx.	Outer Ø mm, approx.	Cu factor per km	Weight kg/km, approx.
21065	2 x 2 x 0.14	26	8.3	31.0	95.0
21066	3 x 2 x 0.14	26	9.2	34.0	105.0
21067	4 x 2 x 0.14	26	10.2	45.0	140.0
21068	5 x 2 x 0.14	26	11.1	58.0	160.0
21069	6 x 2 x 0.14	26	12.3	67.0	185.0
21070	7 x 2 x 0.14	26	12.3	78.0	230.0
21071	8 x 2 x 0.14	26	14.6	97.0	245.0
21072	9 x 2 x 0.14	26	15.8	101.0	280.0
21073	10 x 2 x 0.14	26	16.0	108.0	325.0
21074	12 x 2 x 0.14	26	16.7	134.0	380.0

Part no.	No. cores x cross-sec. mm ²	AWG, approx.	Outer Ø mm, approx.	Cu factor per km	Weight kg/km, approx.
21075	16 x 2 x 0.14	26	18.6	179.0	440.0
21076	20 x 2 x 0.14	26	21.0	225.0	520.0
21077	2 x 2 x 0.25	24	9.5	62.0	125.0
21078	3 x 2 x 0.25	24	10.6	78.2	140.0
21079	4 x 2 x 0.25	24	11.5	124.1	205.0
21080	5 x 2 x 0.25	24	13.0	137.6	230.0
21081	6 x 2 x 0.25	24	14.3	148.1	275.0
21082	7 x 2 x 0.25	24	14.3	159.1	295.0
21083	8 x 2 x 0.25	24	16.8	178.7	330.0
21084	10 x 2 x 0.25	24	18.4	213.9	420.0

PAAR-TRONIC-CY-CY

colour code DIN 47100, EMC-preferred type



Part no.	No. cores x cross-sec. mm ²	AWG, approx.	Outer Ø mm, approx.	Cu factor per km	Weight kg/km, approx.	Part no.	No. cores x cross-sec. mm ²	AWG, approx.	Outer Ø mm, approx.	Cu factor per km	Weight kg/km, approx.
21085	12 x 2 x 0.25	24	19.4	238.3	465.0	21098	14 x 2 x 0.34	22	21.5	388.4	600.0
21086	16 x 2 x 0.25	24	21.6	291.4	590.0	21099	16 x 2 x 0.34	22	22.6	425.5	637.0
21087	20 x 2 x 0.25	24	24.3	325.0	620.0	21100	24 x 2 x 0.34	22	28.6	577.1	781.0
21088	24 x 2 x 0.25	24	27.4	367.5	690.0	21101	2 x 2 x 0.5	20	11.2	83.1	143.0
21089	32 x 2 x 0.25	24	30.3	588.0	785.0	21102	3 x 2 x 0.5	20	12.3	106.4	179.0
21090	48 x 2 x 0.25	24	36.3	840.5	970.0	21103	4 x 2 x 0.5	20	13.9	158.0	241.0
21091	2 x 2 x 0.34	22	10.1	73.1	139.0	21104	6 x 2 x 0.5	20	16.7	201.4	319.0
21092	3 x 2 x 0.34	22	11.0	88.1	157.0	21105	8 x 2 x 0.5	20	20.0	311.5	441.0
21093	4 x 2 x 0.34	22	12.2	137.2	213.0	21106	10 x 2 x 0.5	20	21.9	334.5	464.0
21094	6 x 2 x 0.34	22	15.0	174.8	308.0	21107	12 x 2 x 0.5	20	22.8	394.1	529.0
21095	8 x 2 x 0.34	22	17.6	247.2	385.0	21108	14 x 2 x 0.5	20	24.1	446.0	641.0
21096	10 x 2 x 0.34	22	19.5	288.7	433.0	21109	16 x 2 x 0.5	20	25.5	501.2	694.0
21097	12 x 2 x 0.34	22	20.3	321.0	495.0	21110	24 x 2 x 0.5	20	32.1	712.4	930.0

کابل مدباس PAAR-TRONIC-CY-CY هلوکیبل یک کابل کنترل و سیگنال با عملکرد بالا است. این کابل با طراحی دقیق، روکش PVC مقاوم و شیلد بافته شده از سیم مسی گزینه ای قابل اعتماد برای کاربردهای صنعتی حساس به تداخل الکترومغناطیسی است.

Part Number: 21065

کابل مدباس با کد: 21065